

Rec'd PCT/PTO 01 FEB 2005



10/523378

PCT/IB 03/03308

#2

24.07.03



INVESTOR IN PEOPLE

REC'D 29 AUG 2003

WIPO

PCT


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

20 May 2003

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

THE PATENT OFFICE  
A  
- 6 AUG 2002

The  
Patent  
Office

1/77

request for grant of a patent  
see notes on the back of this form. You can  
also get an explanatory leaflet from the Patent  
Office to help you fill in this form)

The Patent Office  
Cardiff Road  
Newport  
Gwent NP10 8QQ

Your reference

PHGB020126

06AUG02 E738743-3 D02879  
P0177700 0.00-0218174.1

Patent application number  
(The Patent Office will fill in this part)

0218174.1

- 6 AUG 2002

Full name, address and postcode of the or of  
each applicant (underline all surnames)

KONINKLIJKE PHILIPS ELECTRONICS N.V.  
GROENEWOUDSEWEG 1  
5621 BA EINDHOVEN  
THE NETHERLANDS

Patents ADP Number (if you know it)

7586605002

If the applicant is a corporate body, give the  
country/state of its incorporation

THE NETHERLANDS

Title of the invention

A NETWORK ESTABLISHMENT AND MANAGEMENT PROTOCOL

Name of your agent (if you have one)  
"Address for service" in the United Kingdom  
to which all correspondence should be sent  
(including the postcode)

Richard C TURNER  
Philips Intellectual Property and Standards  
Cross Oak Lane  
Redhill  
Surrey RH1 5HA

Patents ADP number (if you know it)

8359655001

If you are declaring priority from one or more  
earlier patent applications, give the country  
and the date of filing of the or of each of these  
earlier applications and (if you know it) the or  
each application number

Country

Priority Application number  
(if you know it)

Date of filing  
(day/month/year)

If this application is divided or otherwise  
derived from an earlier UK application, give  
the number and the filing date of the earlier  
application

Number of earlier application

Date of filing  
(day/month/year)

Is a statement of inventorship and of right to  
grant of a patent required in support of this  
request? (Answer "Yes" if:

YES

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an  
applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

**Patents Form 1/77**

1. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document.

Continuation sheets of this form

Description	30	
Claims(s)	15	
Abstract	1	CP
Drawings	6 only	

2. If you are also filing any of the following, state how many against each item:

**Priority Documents**

Translations of priority documents  
Statement of inventorship and right  
to grant of a patent (*Patents Form 7/77*)  
Request for preliminary examination and  
search (*Patents Form 9/77*)  
Request for substantive examination  
(*Patents Form 10/77*)  
Any other documents  
(*Please specify*)

I/We request the grant of a patent on the basis of this application.

Signature

*Richard Turner*

Date *5.8.02*

Name and daytime telephone number of  
person to contact in the United Kingdom

01293 815492

(R. Turner)

**Warning**

If an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been refused.

**Notes**

If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

Write your answers in capital letters using black ink or you may type them.

If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.

If you have answered "Yes" Patents Form 7/77 will need to be filed.

Once you have filled in the form you must remember to sign and date it.

For details of the fee and ways to pay please contact the Patent Office.

## DESCRIPTION

**A NETWORK ESTABLISHMENT AND MANAGEMENT PROTOCOL**

5           This invention relates to a network protocol, and in particular to implementations of the protocol.

          A prior art protocol for network management is universal plug and play (uPnP), which is very useful for internet applications where bandwidth, battery  
10   consumption, and to an extent cost, are not an issue. Implementations of the protocol in consumer electronics (CE) do exist, but because of the extent of the protocol, such implementations impose a heavy load especially on the simplest devices that otherwise would require only minimal processing capability.

15           The need therefore exists for a protocol suitable for embedding in simple devices such as lights, thermostats and CE equipment (remote control for TV's, DVD's and PVR's), that is simple and cost effective to implement, requires the minimum of bandwidth, yet is scalable across a range of devices with varying capabilities.

20           This need is not restricted to wireless application, but extends to wired applications.

          According to a first aspect of the invention there is provided a system, comprising: a plurality of networked devices each having a transceiver for  
25   sending and receiving network messages; at least one networked device arranged to send a simple device query message to other devices and to receive and interpret simple device description messages subsequently received from the other devices; at least one networked device arranged to send an extended device query message to other devices and to receive and  
30   interpret extended device description messages subsequently received from the other devices; each of the networked devices being arranged to respond to an incoming simple device query message from another of the devices by

5 sending a simple device description message of defined length including a device type value representing the type of the device; and at least one of the networked devices is arranged to respond to an incoming extended device query message from another of the devices by sending an extended device description message.

Such a method implements the protocol that is the subject of this patent application. The protocol itself will be referred to as home universal control language (HUCL).

10 In comparison, those prior art methods of which the inventors are aware implement only a single device description message and response. By providing a simple device description of defined length and an extended device description of variable length the invention makes it possible to combine using the HUCL protocol simple devices operating only using the simple messages and complex devices which make use of the greater  
15 functionality available from the extended device description of variable length. Simple devices may simply ignore extended device description queries.

The Simple Device Description includes a small or moderate number of predetermined fields each field being of fixed length. In general, the same fields will be used for each message, although there may be some variation.  
20 For example, a composite device may include an additional integer field including the number of sub-devices as explained below.

Preferably, the simple device description message is in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the  
25 other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not  
30 including any further level of subsidiary device types depending from the controller device type.

According to the HUCL protocol, the underlying message format is a human readable format, such as XML. However, to save bandwidth, messages are passed between networked devices in compressed form. A networked device is nevertheless able to process such compressed messages, because the compression method used is token compression, which replaces common strings with tokens. The networked device can thus recognise the compressed tokens without decompression, at least enough to recognise a query requiring a response of a simple device description, and then respond with a simple device description. Thus, a networked device can be implemented with little overhead.

A suitable form of token coding is described in "wap binary XML content format" of 24 June 1999, available at <http://www.w3.org/TR/wbxml>.

It will be noted that although there is at least one hierarchy depending from a basic device type, i.e. a hierarchy of controlled devices, there is no corresponding hierarchy of controller devices. This is to keep the simple device description messages as short and simple as possible - many controllers, such as a universal remote control, are capable of controlling a number of different device types.

Preferably, the plurality of networked devices include at least one simple device without the capability to decompress messages and accordingly which interprets directly compressed messages and at least one complex device including a message decompression arrangement for decompressing the messages and a message interpreter for interpreting the decompressed messages.

According to a second aspect of the invention there is provided a system, comprising a plurality of networked devices each having a transceiver for sending and receiving network messages; wherein each networked device has a predetermined device type selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including

any further level of subsidiary device types depending from the controller device type; at least one of the networked devices is a controller; and at least one of the networked devices is a controlled device having a device type of the basic device type or a device type depending from the basic device type.

5       The hierarchy of device types of the second aspect again facilitates operation with both simple and complex devices. The limitation of the controller device type to a single device type greatly reduces the number of different devices types that a simple controlled devices needs to recognise.

10       Preferably, the predetermined top level elements further include a composite device type; the system includes at least one networked device of the composite device type having the functionality of a integer number of other devices, and each of the at least one networked device of the composite device type responds to an incoming device query message requiring a simple device description by sending a simple device description including the device  
15       type as a composite device and a sub-device number representing the number of other devices.

20       In a preferred arrangement the networked devices discussed above form a first network, and the system further includes a second plurality of the networked devices arranged as a second network, wherein one of the networked devices is a bridge device in both the first and second networks, wherein the bridge device is arranged to respond to requests from the first network for a simple device description by responding with a simple device description including the device type as a composite device and a sub-device number representing the number of other devices in the second network.

25       As well as the system, the invention also relates to the individual devices and methods of operation.

30       According to a third aspect of the invention, there is provided a method of operation of a networked device, including: establishing the address of at least one other device; sending a simple device description query message to one of the other devices requesting a simple device description; receiving from the other device a simple device description message of defined length including a device type value representing the type of the other device and a

field indicating whether an extended device description is available; testing the simple device description message to determine whether an extended device description is available, and if so sending an extended device description query message to the other device requesting an extended device description  
5 from the other device; and receiving from the other device an extended device description of variable length.

In a fourth aspect, the invention relates to a method of operation of a networked device, including: establishing the address of other devices; sending a simple device description query message to one of the other  
10 devices requesting a simple device description; receiving from the other device a simple device description message of fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type  
15 value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of  
20 subsidiary device types depending from the controller device type.

In a fifth aspect, the method relates to a method of operation of a networked device, including: receiving a simple device description query message from another device requesting a simple device description;  
sending to the other device a simple device description message of  
25 fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller  
30 device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not



including any further level of subsidiary device types depending from the controller device type.

5 In a sixth aspect, the invention relates to a method of operating a networked device, including: receiving token-compressed messages; recognising in the received token-compressed messages incoming simple device description query messages requiring a simple device description response from the networked device, without decompressing the incoming messages; and sending a simple device description including a device type as a response to an incoming device query message requiring a simple device  
10 description response.

The token-compressed messages are preferably compressed from a human-readable message format such as XML. The individual words and field markers of the message format are replaced by tokens.

15 In a further aspect, the invention relates to a networked device, including: a transceiver for sending and receiving messages; a message handler arranged to carry out the steps of: initiating discovery; establishing the address of at least one other device; sending a simple device description query message to another device; requesting a simple device description; receiving from the other device a simple device description message of  
20 defined length including a device type value representing the type of the other device; sending an extended device description query message to the other device requesting an extended device description from the other device; and receiving from the other device an extended device description of variable length.

25 In a yet further aspect, the invention relates to a networked device, including: a transceiver for sending and receiving messages; a message handler arranged to carry out the steps of: establishing the address of at least one other device; sending a simple device description query message to another devices requesting a simple device description; receiving from the  
30 other device a simple device description message of fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a

device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

A controller device according to the invention preferably includes a control input, and controls other devices based on signals received on the control input. Further, the controller device may implement one or more ways of determining what devices the controller can control.

One approach to deal with the lack of information given by the fact that a device is a controller device type is for the controller device to have the functionality to respond to an incoming controller query message querying whether the controller can control a predetermined device type by responding with the lowest level of device type in the list of device types that can be controlled by the networked device that either is the predetermined device type or is a higher level device type from which the predetermined device type depends. The controller device can then send control signals selected from a predetermined list of control signals to other devices in accordance with signals received on the control input.

Instead of being a controller device, the device may be a controlled device having a device type of the basic device type or a device type depending from the basic device type; the networked device having the capability of responding to basic device instructions sent by a controller, the instructions including at least a predetermined base set of instructions.

In order to cope with multifunctional devices, the predetermined top level elements may include a composite device type.

Networked devices of the composite device type have the functionality of a predetermined number of other device types, and are arranged to respond to an incoming device query message requiring a simple device description by

sending a simple device description including the device type as a composite device and the instantaneous number of other device types.

The networked device may include a memory storing a predetermined simple device description message, wherein the description message is a message pre-compressed from a message in human readable form including a device type; a flag indicating if the sending device has an extended device description available; and a predetermined number of additional flags identifying a predetermined number of additional status settings. Thus, rather than generating a simple device description message internally, a suitable message is pre-stored and sent out when required.

In another aspect, the invention relates to a networked device, including: a transceiver for sending and receiving messages; a message handler arranged to carry out the steps of: receiving a simple device description query message from another device requesting a simple device description; and sending to the other device a simple device description message of fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

In another aspect, the invention relates to a networked device, comprising a transceiver for sending and receiving token-compressed human readable messages; and a message parser arranged to carry out the steps on incoming token-compressed human readable messages of: recognising received device query messages requiring a simple device description response from the networked device, without decompressing the incoming messages; and sending through the transceiver a simple device

description including a device type as a response to an incoming device query message requiring a simple device description response.

The invention also relates to a method of operating a network including controller devices and controlled devices, the method comprising: establishing  
5 in a specific controller device a list of network addresses of devices in the network; sending a query message requiring a simple device description response from the specific controller device to another of the devices; sending from the other device to the specific controller device a simple device description message indicating the device type, wherein the device type is  
10 selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device  
15 types depending from the controller device type; determining the extent to which the specific controller device can control the other device by determining the lowest level of device type that either is the device type of the other device or is a higher level device type from which the device type of the other device depends; and controlling the other device by the specific controller device with  
20 the functionality of the determined lowest level of device type by sending control signals from the specific controller device to the other device selected from a list of control signals appertaining to the determined lowest level of device type.

The invention also relates to a computer program for controlling a  
25 networked device.

In another aspect, the invention relates to a computer program for controlling a controller-type networked device, the networked device having a transport stack and an application, the computer program comprising: code implementing a transport adaption layer for interfacing with the transport stack;  
30 code implementing an application programming interface for interfacing with the application; and code implementing a messaging layer including the capabilities of sending and receiving messages in a token-encoded human

readable messaging format, the code being arranged to cause the networked device: to recognise incoming device query messages requiring a simple device description response and to provide a simple device description response including a device type of controller device type; to respond to an incoming controller query message querying whether the networked device can control a predetermined device type by responding with the lowest level of device type in the list of device types that can be controlled by the networked device that either is the predetermined device type or is a higher level device type from which the predetermined device type depends; and to carry out the steps of: sending a device query message to another device; receiving a response from the other device indicating the device type of the other device, the device type being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type; determining the extent to which the networked device can control the other device by determining the lowest level of device type that either is the device type of the other device or is a higher level device type from which the device type of the other device depends, in the list of device types that can be controlled by the networked device; and controlling the other device with the functionality of the determined lowest level of device type by sending control signals selected from a list of control signals appertaining to the determined lowest level of device type.

In another aspect, the invention relates to a computer program for controlling a networked device, the networked device having a transport stack and an application, the computer program comprising: code implementing a transport adaption layer for interfacing with the transport stack; code implementing an application programming interface for interfacing with the application; and code implementing a messaging layer including the capabilities of sending and receiving messages in a token-encoded human

readable messaging format, the code being arranged to cause the networked device: to recognise incoming device query messages requiring a simple device description response and to provide a simple device description response including a device type selected from a device type hierarchy having  
5 predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller  
10 device type; and to respond to basic device instructions sent by a controller.

The computer program may be recorded on a data carrier.

The invention also relates to a simple device description message signal, including in token-compressed XML the following data: a predetermined number of bits storing a device type; a field indicating if the  
15 sending device has an extended device description available; and a number of additional fields identifying a predetermined number of additional status settings.

Some of the additional fields may be optional. For example, the message may include a field to indicate the number of sub-devices of a  
20 composite device. To reduce network overhead, this field may be included only in the case of a message with the device type recorded as composite.

Such a message signal implements the simple functionality provided by HUCL.

The system may include a number of simple devices, with simple  
25 functionality and no capability to decompress messages, and more complex devices that decompress messages to interpret them and operate on them. The more complex devices can have much more complex functionality, at the expense of increased overhead and processor power requirement.

In another aspect, the invention relates to a network establishment and  
30 management protocol for controlling electronic devices, the protocol being recorded on a record medium, the protocol comprising: a compression algorithm defining the mechanism for compression of said messages; a

definition of a generic message format, the messages being XML compliant messages; and a definition of message sequencing requirements.

The protocol may define controller devices and discovery for controller devices may be defined to include a mechanism for discovering a controlling  
5 device and instructing said controlling device on its future operation.

The protocol may further define device description messages to be one of a first message of fixed length and content, and a second message of undefined length and content.

The protocol may define discovery of device description messages to  
10 allow piecemeal discovery of the second device description message.

The protocol may define composite devices and the device description messages of composite devices are defined to include the number of sub-devices in the composite.

Discovery of device description messages of composite devices may be  
15 defined to allow discovery of the sub-devices in turn.

For a better understanding of the invention, embodiments will now be described purely by way of example, with reference to the accompanying drawings in which:

20 Figure 1 shows a pair of devices communicating using an embodiment according to the invention;

Figure 2 shows a schematic of the software in one device;

Figure 3 is a flow diagram of the device discovery process;

Figure 4 is a schematic of the device type hierarchy;

25 Figure 5 shows the steps that a controller carries out to inform a controlled device of its control capability of that device;

Figure 6 shows the steps that a controller carries out to determine its control capability of a controlled device;

30 Figure 7 is a flow diagram of the device discovery process for a composite device;

Figure 8 illustrates an embodiment of a composite device;

Figure 9 illustrates another embodiment of a composite device;

Figure 10 shows the structure of the software;  
Figure 11 shows an embodiment of a system having a bridge device;  
Figure 12 shows an embodiment of a system connected to the internet;  
5 Figure 13 shows an embodiment of a system having a bridge device  
between a network according to the invention and another network;  
Figure 14 illustrates the HUCL protocol; and  
Figure 15 illustrates a simple device description message.

10 The protocol HUCL is a lightweight, low bandwidth control protocol  
primarily designed for wireless systems. The messaging format is based on  
XML, and messages are compressed prior to transmission. The use of XML  
provides an extensible and scalable solution with the compression reducing  
the data sent, so reducing the amount of time the transmitter is on and  
15 consuming power.

The general principles of the HUCL protocol and how it would operate  
on a device will now be discussed with reference to a simple example.

Referring to Figure 1, a light switch 2 and a light fitting 4 are provided.  
The light switch 2 has a physical rocker switch 6 operated by the user,  
20 together with an RF transceiver 8 and battery 10, together with control circuitry  
12 and memory 14. The light fitting also has an RF transceiver 8 and memory  
14, but is mains powered and has the control circuitry 20 to apply power to the  
light bulb 22. The light switch 2 is thus an example of a controller which has  
a control input 6 (the switch), whereas the light fitting is an example of a  
25 controlled device 4. The memory 14 in the controller includes a list 24 of  
device types that the controller can control, and control functions appertaining  
to the device types. The memory 14 in both controlled 4 and controller 2  
devices also contains code 26 for causing the control circuitry to carry out the  
methods that will be described in more detail below.



Figure 2 shows a representation of the software that resides on each of the devices in memory 14. The control application 30 communicates with the HUCL Software Stack 32 when certain events occur.

5 In a similar way the HUCL Software Stack 32 communicates with the RF Software Stack 34, and the RF Software Stack 34 will communicate back to the HUCL Software Stack 32 when certain events occur e.g. on receipt of data.

10 Messages 36 are sent and received. The messages may be of a number of types, including a simple device description query message, or any of a number of other message types.

The operation of the devices will now be described with reference to Figure 3. The first phase in the operation of this pair of devices is for the switch to discover the address of the fitting. This is known as device discovery, and it is a requirement of the underlying RF transport stack that device  
15 discovery is either provided (in the RF Software Stack), or that it is possible to implement device discovery on top of the transport stack (in the lower layer of the HUCL Software Stack).

The discovery process is initiated 100 by the Control Application (possibly as a result of some user interaction) by performing a call into the  
20 HUCL Software Stack requesting firstly the number of known devices, and then the network addresses of those devices. These device addresses are returned.

Depending on the underlying RF protocol, the network addresses may be established in some other way.

25 The end result of the device discovery phase is that the Control Application is supplied 102 with a list of addresses of all devices known by the RF Stack. At this point in the process the Control Application knows nothing more about each other device other than its address.

30 The second phase in the pairing process is for the Control Application to gather information on the devices for which it has addresses. This information is called the device description. The control application does this by making a

call into the HUCL Software Stack, passing the address of the device that it requires the device description from.

The request for the simple device description is then passed over the RF link to the destination device, so in the switch / fitting example described above the request is transmitted from the switch to the fitting. On receiving the request, the HUCL Software Stack at the destination device makes a call in to the Control Application requesting the device description. The format of the description is defined. If not already in a compressed form the description is compressed before being transmitted back to the sender of the request.

When the HUCL Software Stack on the requesting device receives the device description, it is passed up to the Control Application. At this point the application has some basic information about the device and can make the decision as to whether it wished to communicate further with this device.

A design goal of HUCL is that it is suitable to operate on very simple devices, however the information necessary to fully describing a device is potentially quite complex. The list below shows the sort of information a device might want to provide as part of its description.

Device Type e.g. DVD

Vendor Name e.g. Philips

Model Number e.g. DVD1010/002

Serial Number e.g. AH06848032345

Vendor URL e.g. www.philips.com

For the simplest of control devices, such as the switch used in the example throughout this section, much of this information is probably redundant. It would however be of use on a higher end 'PDA' type remote control that has a screen where such information could be displayed to the user.

The processing of such descriptions on low-end devices can present a problem, since it would potentially need the storage (RAM) to cache the complete message as it was received. The problem is worse than it might at first seem, since the overall size of the description data shown above is

indeterminate, much of the information is 'free text'; the vendor name could be very long, the URL could specify an exact page maybe even with parameters e.g.

http://www.consumer.philips.com/global/b2c/ce/catalog/subcategory.jhtml?groupId=VIDEO&divId=0&catId=DVD&subCatId=DVDPLAYER

The way in which this is overcome in HUCL is that the device description is split into two tiers of information. The first tier is a simplistic description of the device but identifying if further information is available. It does not contain any free text fields so the overall length of it is deterministic. The second tier of extended information is optional but provides additional information.

Referring to Figure 15, the Simple Device Description message 230 includes as fields the device type 232, a field 238 to indicate if Extended Device Description available and other fields 236 identifying key information e.g. a flag to indicate if event subscription is available. Optional integer field 234 represents the number of sub-devices of a composite device. The skilled person will appreciate that the message 230 may also include a header and footer which are omitted for simplicity. The message will include compressed XML tokens which are likewise omitted for clarity. The fields of the Simple Device Description are all of fixed length, so that they can be dealt with readily without decompression.

After receiving 106 (Figure 3) the Simple Device Description 230 the Simple Device Description 230 is passed back to the HUCL Stack.

The Simple Device Description message in its uncompressed, human readable form may have, for example, the format:

```

...
<HUCL-device srcEmbDevID='0'>
  <embDev ID='X'>
    <embDevType>DeviceType</embDevType>
    <eventService/>
    <extDevDesc/>
  </embDev>
</HUCL-device>
...
```

If the Extended Device Description is available and the controller device requires it, the controller device Control Application may issue a "GetExtendedDescription" request 108 back to the device.

5 The HUCL Stack on the device receiving this request makes a Get Extended Description call into the Control Application requesting the Extended Device Description.

The Extended Device Description is passed back to the HUCL Stack, and makes its way back to the Control Application on the device that requested it. The Extended Description is then returned 110 to the requesting  
10 device.

If a GetExtendedDescription query is received on a device that does not provide an Extended Device Description the request is simply ignored.

Returning again to the switch / fitting example used throughout this section, from the point when the switch knows only the address of the fitting,  
15 the switch requests from the fitting its Simple Device Description. On receiving this it provides sufficient information such that the switch knows that it is talking to a light fitting that conforms to the standard fitting command set, it also knows that (for example) the fitting can't provide any Extended Device Description.

20 It is mandatory for a device application to provide a Simple Device Description to the HUCL Stack when requested. A device that does not provide any Extended Device Description can ignore any requests it receives for such information.

Included in the Simple Device Description returned by a device (when  
25 requested) is the device type field 232 that identifies the type of the device, e.g. TV, DVD, Light Fitting etc. The Device Type field 232 will identify to the controller (requesting the Simple Device Description) the instruction set that the device conforms to. HUCL devices identify themselves simply by their type identifier, they do not then go on to send messages to describe how they are  
30 controlled; there is no 'runtime' service description concept in HUCL. If a device identifies itself as a light fitting then the command set that can be called

on this device is identified on paper in the HUCL specification for a Light Fitting type device.

Referring to Figure 4, all device types depend from a base device type 50. Top level elements 58 include in this example the controller device type 52, a basic device type 54 for controlled devices and an alarm device type 56.

Subsidiary device types 68 depend from the basic device type. In the example, these include a TV device type 64, a dimmable light device type 62 and a PVR device 60.

The Device Type Classification was to produce a system aims to allow a simple controller to identify whether it could control a device to the extent of the controllers' capabilities.

A simple switch could be paired with a light fitting to turn on and off a light, but one might argue that the control functionality of the switch, that is its ability to turn a device on or off should be applicable to any device than can accept an on / off concept e.g. a TV, Heater, Printer.

One way in which this could be implemented is for the switch to have a list of all of the devices it knows how to control (turn On or Off), so when it requests the Simple Device Description for a device, it can look at the Device Type field in the returned description and determine if it is within its list of device types it knows how to control.

There are two significant drawbacks of this approach, firstly the switch is a very simple device and it is undesirable for the application within it to have to hold a list of all possible devices that it could control, which would be quite large; secondly if a new type of device is created after the switch is produced (which can accept simple On Off functionality), then the switch will not have this new device type in its list, and will not believe it can control it i.e. it is not extensible.

HUCL classifies devices in a hierarchical way, shown in Figure 4. The Device Type field 232 (Figure 15) identifies the device within the hierarchy and so even if new devices were created, as long as it is derived from an the appropriate point within the hierarchy, a simple switch would still know that it could control it to an extent.

Devices that fall lower in the tree inherit the functionality of device types above it. It may be necessary to add some interpretation to the commands when applied to lower devices in the tree, for example the On / Off command when sent to a light will fairly obviously turn it On and Off, but the same  
5 commands when sent to a TV would place it in and out of standby mode.

The way in which the Device Type field is constructed to convey where the device sits within the hierarchy is covered in the Protocol Specification. The key result of the Device Type description is that even if the controller has no knowledge of the specific device type itself, it can determine the device  
10 from which it is derived, of which it may have some knowledge and hence may be able to control the device to some lesser extent (from the perspective of the device).

For example, consider the case that a light switch obtains the address of a device, it requests from this device the Simple Device Description; the  
15 Device Type field identifies the device as TV, but the switch does not recognise this as a device it knows about. However the switch can also establish from the description that it is a derivative of the 'Basic Device', which it does know about. The net result is that the switch can control the TV, to the extent of the controllers capabilities i.e. On and Off, despite knowing nothing  
20 about the device itself. The device could be a brand new category of device called an 'XYZ' invented long after the switch was manufactured, but so long as it is derived from a Basic Device the switch can still control it to an extent.

Although the Device Type Hierarchy may have just two tiers, and controller and basic device top level elements, at least one further tier and/or  
25 top level element is desirable. This caters for devices that would not comply with the functionality shown above in the Basic Device that is devices that do not have basic 'Turn On' 'Turn Off' functionality, e.g. an alarm. For illustrative purposes an 'Alarm' type device 56 has been shown in Figure 4 and understandably this 'Alarm' device does not want to implement the normal On /  
30 Off functions that devices that are derived from Basic Device must have; it therefore sits at the same top level 58 in the hierarchy as the Basic Device 54 itself.

A second extension to the hierarchy is also shown in Figure 4 i.e. the Enhanced TV Device 66 below the normal TV Device 64. Here the Enhanced TV Device inherits all of the functionality of both the Basic Device 54 and the TV Device 64, but also includes some extended functionality that is not present in a normal TV. A regular TV remote control designed to operate a normal TV Device can operate the Enhanced TV Device to the level of a normal TV Device functionality, but can't control the extended functionality.

The HUCL protocol accordingly provides an extensible mechanism for describing the Device Type and the devices above it from which it inherits functionality. Whilst the idea of a hierarchy of many layers might seem appealing, extending it beyond three or four levels will start to impact the size of the Simple Device Description.

Within HUCL it is possible to request a device description from a controller as well as a controllable device. When one device sends the "Get Simple Description" to a controller device (e.g. a switch) it is returned a Simple Device Description that contains a Device Type of "Controller". The controller device may also make available an Extended Device Description which provides further information such as the manufacturer, model number etc.

It is important to note that the Device Type returned by a controller device is simply "Controller" 52 there is no hierarchy of different controller type devices defined in the device type tree. The reason for this is again trying to keep the protocol and messages sizes small and simple. It might be felt that it would be possible to have different controller types derived from the basic Controller such as a Switch, TV Remote Control, PVR Remote Control, etc. However a problem would occur with intelligent controllers such as Universal Remote Controller that are capable of controlling a wide range of devices. To include all of the possible controller types in a simple device description would result in a potentially large message, which goes against the ideal of trying to make the initial Simple Device Description simple. To determine the exact capabilities of a controller device different mechanisms are employed.

The first means of determining the capabilities of a controller device is by the Extended Device Description which is permitted on a controller device.

and may contain information such as the device name e.g. "Universal Remote Control" and whilst this is textual information and is not directly interpretable by application software, it can be presented to the user to assist in making an informed choice about a controller.

5       The second means for a device to determine more about a controller is by querying it.

      The use of querying is a powerful mechanism for drip-feeding information about a device that would otherwise, if supplied en-mass, overload the requestor.

10       Each device of controller type provides a means for other devices to query 120 whether it is able to control a specific Device Type (Figure 5). The device type passed in the query is the same field as is used in the Simple Device Description i.e. as defined in the Device Type Hierarchy. The controller returns 122 the level to which it can control the device, by returning the lowest  
15       device type in a list stored in the controller memory 14 that is the device type passed in the query or from which that device type depends. For example, a simple switch is queried whether it can control an Enhanced TV Device. Based on the hierarchy illustrated in Figure 4 above the reply is that it can control it to the level of Basic Device. The switch would typically itself know  
20       nothing about a device type of Enhanced TV Device, but since the Device Type also includes the inherited devices it would be able to identify the Basic Device and return this as the lowest hierarchically superior device type it is capable of controlling.

      The controller also implements an algorithm to determine if the switch  
25       can control a device type that is returned to it in a Simple Device Description (Figure 6). When a switch discovers the address of a device it asks 124 the device for its simple device description, on receiving this information 126 the switch tests 128 whether it can control a device of this type to any degree, which is the same question it needs to respond to as a result of the querying  
30       process 120. The result is that the two query processes 120, 122, 124, 126, 128 do not add too much to the complexity of the simple switch device. The same applies to other simple devices.



It can be foreseen that there will be instances where a device may be a composition of a number of discrete devices all accessed via the same physical address e.g. all co-located on a single RF transceiver.

Examples of this type of device are a bank of individually switchable lights controlled through a single RF transceiver, or a TV with integrated alarm clock where both components are remotely controllable again through the same transceiver.

Figure 7 illustrates the discovery process. The switch initially obtains the addresses of all devices known by the underlying transport medium, this includes the single address of the four individually controllable lights. The switch issues 140 a Get Simple Description command to the light bank, and the question that arises is what should the reply be? If four device descriptions are returned then this would be four times as much data than the switch would be expecting to receive. Returning multiple Simple Device Descriptions is not very scalable, and would, for example cause problems if there were 20 lights in the lighting bank.

The solution for this provided by HUCL is a specific Device Type for composite devices.

The composite device returns 142 its Simple Device Description including in the Device Type field 232 its device type as a "Composite Device". The Simple Device Description also identifies in field 234 that there are, in this example, four embedded devices within this single device.

The next stage once the controller has identified that it is communicating with a composite device is for it to establish what devices are embedded within it. The controller makes 144 further Get Simple Description requests to the composite device but addressing the requests to the specific embedded devices. The embedded devices return 146 their device descriptions.

Once the controller decides that it is going to control one of the embedded devices, all control commands are directed at the specific embedded device by including an embedded device ID with each command.

Once the concept of the composite device has been established it opens up the possibility for a number of interesting device combinations that would be of benefit, some of these will be discussed below.

5 An example is a single device that consists of a lamp with integral switch, where the functionality of switch is exposed so as to be able to control other devices. This device, when queried for its Simple Device Description exhibits itself as a composite device, but when queried further one embedded device would be found to be a controller, and the other a controllable i.e. a Light Device. A number of such devices could be configured in such a way that  
10 operating the switch on any one of the devices causes the lights to be turned On / Off on all the devices e.g. turning on any one table lamp in the lounge causes all the table lamps in the lounge to come on.

Other possible combinations of composite device within the CE domain include for example a TV + video cassette recorder (VCR) or DVD and VCR.  
15 Each of these could if required describe itself as a composite of two devices.

Conceptually a Device consists of the core device plus zero or more sub-components, e.g. a TV Device 60 may for example consist of the TV Device 60 itself plus Tuner 64, Audio 66 and Display 68 sub-components (see Figure 8).

20 It is also conceivable that a single device may have more than one instance of a sub-component e.g. a TV / VCR Combi Device may have two tuners 62, 64, one for the TV and one for the VCR (see Figure 9), as well as audio 66 and display 68 components.

It might be felt that the use of XML and its compression and de-  
25 compression on the simplest of devices is a little heavyweight. The use of XML to describe the protocol provides a solution that is easily extensible for future enhancements, relatively simple to describe and understand, can easily handle structured information and is instantly compatible with the 'internet domain'.

30 Using a tagged compression technique on the XML (defined within HUCL) takes the relatively verbose protocol back down in size towards that of

a traditional pure binary-based protocol, with some additional overhead to retain the content structure.

If one were to be presented with the a command in its compressed form it can be read in a similar manner that one would read any other binary based  
5 protocol, using information on the command structure and a table of definitions for data values. The only hint that the binary data may have originated from an XML based notation would be the presence of data to represent structure.

The HUCL specification defines that the messages is always transmitted through the transport medium in its compressed form. However on  
10 a simple device the application may operate directly on compressed messages, so eliminating the need on that device for the presence of the compression / de-compression software within the HUCL Software Stack. In this case the application would store (as part of the application image in ROM) the simple device description in its pre-compressed form, it would have a  
15 parser for the compressed protocol messages that it receives which would be similar in nature to any other binary protocol parser; any response messages would also need to be stored in their compressed form.

Using this approach the simplest devices such as the light switch and light fitting example used throughout this section can be implemented with a  
20 reduced software stack, and given that the number of commands that a simple device would need to understand and send is relatively small (turn light on, turn light off, toggle, get current state, get device description etc.) the overhead on the application software is minimal.

This offers a scalable solution to devices, where it is practical to  
25 implement the application to operate on compressed data this can be done, but when the device becomes more complex there will be a point where it becomes easier to include the compression / de-compression functionality in the stack and have the application use the protocol messages in their full XML notation. This cut off point is entirely down to the device designer and not  
30 defined or dictated by HUCL at all.

Figure 10 illustrates how the components that make up HUCL fit together. It will be appreciated that the components are software components recorded in memory.

5 The following sections discuss in more detail the layers that form the HUCL software stack 32 and the functionality that they provide.

As has been stated earlier HUCL does not rely on a specific transport protocol (unlike for example TCP/IP) but instead sits directly on top of a transport stack 34. Different transport stacks 34 will by their nature offer differing services to applications and through differing API's; the HUCL  
10 Transport Adaption Layer 180 acts as a buffer to the specific transport layer.

The Transport Adaption Layer 180 provides to the higher layers in the HUCL stack a consistent transport independent set of services. The requirements of this layer are defined in detail in the Protocol Specification.

The messaging layer 182 provides the bulk of the functionality of the  
15 HUCL Software Stack. Applications communicate with this layer through the HUCL API and it will perform the calls back in to the application when necessary (e.g. when data is received).

The messaging layer 182 also handles any initial error reporting and if necessary acknowledgements. Message ID's and Transaction ID's used to  
20 check for missing messages and for coupling messages to replies are also handled fully by this layer.

The Messaging layer 182 also makes use of the Compression / Decompression services 184 as and when a message needs to be compressed or decompressed. As discussed earlier an application deals  
25 exclusively with messages in their compressed form, no calls are made to these services and they can be removed from the runtime stack.

Quite simply the compression and decompression services provide the message layer with the means to convert the HUCL messages between their compressed and decompressed forms. It is possible for this component of the  
30 system to be absent in low-end devices where all data exchanges with the application are made with compressed messages.

The application programming interface API 186 is the interface through which all applications communicate with the HUCL software Stack. Communication is bi-directional in that the HUCL stack will make asynchronous calls back to the application as a result of certain events  
5 occurring in the lower layers e.g. message received via the transport stack.

HUCL is transport stack 34 independent, and what this means is that the HUCL messaging protocol can be built on top of a variety of transport stacks, both wired and wireless.

Since HUCL is designed as a lightweight protocol it is therefore most  
10 suited to lightweight transport stacks as well such as the emerging Zigbee (802.15.4) standard, but it can sit equally well on top of TCP & UDP /IP which opens up a wide range of other protocols, both wired (e.g. Ethernet) and wireless (e.g. 802.11b).

For a HUCL to be implemented on a transport stack 34 it must be  
15 possible to provide a number of services to the messaging layer of the HUCL stack. This means that these services can either be present in the transport stack itself or it must be possible to implement any missing services in the Transport Abstraction Layer of the HUCL stack. These services may cover aspects such as addressing, message delivery and device discovery (e.g.  
20 discovering the addresses of other devices on the network).

Bridging between different networks is an important part of any protocol. There is never going to be a single network protocol and transport medium adopted universally.

From the perspective of HUCL there are two distinct types of bridging  
25 possible; firstly that between different transport stacks where HUCL is the common protocol being used on both, and secondly bridging between different protocols.

HUCL transport stack bridging is necessary when a number of HUCL devices exist that need to communicate with each other but that use different  
30 underlying transport stacks or networks 210, 212. The illustration below highlights one such example.

Figure 11 above shows a scenario where a number of devices 200 all use the HUCL protocol. Some of these devices 202 operate over Zigbee 210 and others 204 operate over 802.11b 212, so whilst all the devices 'speak the same language' (HUCL) the Zigbee devices 202 are unable to communicate  
5 directly with the 802.11b 204 devices because of the different transport network.

The bridge in this situation consists of a bridge device 206 with both a Zigbee and 802.11b transceiver, on top of these the HUCL bridge software resides. Since the whole network is all based on HUCL the job of the bridge is  
10 primarily that of a router. The bridge has a first transceiver 224 for communicating with devices in the Zigbee network 210 and a second transceiver 226 for communicating with devices in the second network 212. Although only one device 202 other than the bridge 206 is shown in the first network, there may of course be many more devices.

15 The use of the composite device type can greatly simplify a bridge in HUCL. At the lowest level the bridge appears on each of the networks as a single physical address. When a device discovers the bridge address it first, as always, requests device information through the Get Simple Description request. The bridge responds directly to this and identifies itself as a  
20 Composite Device and returns the number of devices located on the 'other side' of the bridge.

Further queries are then made to the bridge requesting the Simple Device Description for each of the 'pseudo' embedded devices, just as if it were any other composite device. The requests and subsequent commands  
25 are all identified as being for a specific embedded device within the bridge however they are then forwarded on by the bridge to a specific device located on the 'other side'.

The bridge is not quite a normal composite device since the number of embedded devices that it contains may change; it is a Dynamic Composite.  
30 The bridge identifies the number of embedded devices as a part of the standard response to a Get Simple Description request, but this is the instantaneous number of devices located on the other side of the bridge. The

Dynamic Composite also exposes an attribute that identifies the number of devices on the other side, so that devices can query this at any time. If the bridge supports event subscription, devices can also subscribe to changes in this attribute so as they are informed when the number of devices changes.

5        A Home Gateway that would allow devices within a home network to be controlled from outside would be implemented as a type of bridge. The scenario illustrated in Figure 12 shows a gateway 220 connected to the outside world via a wired IP based transport, and connecting devices in the home on both Zigbee 210 and 802.11b 212.

10        Commands and requests from the outside IP domain 222 are directed to the Home Gateway using a conventional IP address scheme (IPv4 or IPv6), once they arrive the devices within the home are represented as embedded devices contained within the Gateway, and commands and requests are directed to these via the normal mechanism used on any composite device.  
15        Internally the Gateway has a table mapping the embedded device number with real device addresses located on one of the two possible networks. The Gateway then forwards on requests to the correct device.

      The second distinct type of bridging is that of Protocol Bridging where the protocol itself (and possible the transport medium) is different on two or  
20        more networks, this is illustrated in Figure 13. The Protocol Bridge 220 can understand the messages and convert them from one protocol to the other. However, the use of the composite device concept to present devices to the HUCL network that are physically present on the other protocol may be used as above.

25        It is intended that HUCL shall adopt the addressing scheme of the underlying transport stack. By doing this the complexity of devices and the sizes of messages can be kept to a minimum. The mechanism for accessing devices that reside on different physical transport mediums is already covered in section 5.1.1, and it will only be these bridge type devices that require an  
30        address table.

      The protocol itself is a document recorded on a medium 214, including the following information as shown in Figure 14:

a generic HUCL message format 200 that defines the format to which all HUCL messages conform;

message definitions 202 defining the specific messages that form the control protocol.

5 message sequencing requirements 204 defining which messages are sent when, and the requirements of the application on receiving a message.

the HUCL API definition 206 defining the bi directional interface between HUCL and the application using it;

10 the messaging System requirements and functionality 208 of the HUCL software stack;

a compression algorithm 210 defining the mechanism for the compression of the HUCL messages, and

a transport Adaption Layer definition 212 defining how the HUCL software stack is interfaced to a transport system (e.g. an RF stack).

15 HUCL is accordingly not simply a message format definition but also encapsulates a message interchange and compression. The later four items in the list above form the HUCL software stack that would be present in a device, the first three items define the requirements to which the stack and application must conform.

20 From reading the present disclosure, other variations and modifications will be apparent to persons skilled in the art. Such variations and modifications may involve equivalent and other features which are already known in the design, manufacture and use of networks and which may be used in addition to or instead of features described herein. Although claims have been  
25 formulated in this application to particular combinations of features, it should be understood that the scope of disclosure also includes any novel feature or any novel combination of features disclosed herein either explicitly or implicitly or any generalisation thereof, whether or not it mitigates any or all of the same technical problems as does the present invention. The applicants hereby give  
30 notice that new claims may be formulated to any such features and/or combinations of such features during the prosecution of the present application or of any further applications derived therefrom.



In particular, the specific subroutine names used in the examples may readily be varied. The computer program controlling the devices is shown as being recorded in memory 14 but the skilled person will realise that it could be recorded on many other types of record carrier such as a CD, floppy disc, etc.

5 Further, it will be noted that a very simple example of a light fitting and light switch has been extensively described in the forgoing. The skilled person will appreciate that many more complex control scenarios are also possible.

## CLAIMS

1. A method of operation of a networked device, including:

establishing the address of at least one other device;

5 sending a simple device description query message to one of the other devices requesting a simple device description;

receiving from the other device a simple device description message of defined length including a device type value representing the type of the other device;

10 sending an extended device description query message to the other device requesting an extended device description from the other device; and

receiving from the other device an extended device description of variable length.

15 2. A method according to claim 1 wherein the simple device description message is in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top  
20 level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

25

3. A method of operation of a networked device, including:

receiving the address of other devices;

sending a simple device description query message to one of the other devices requesting a simple device description;

30

receiving from the other device a simple device description message of defined length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message

format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

4. A method according to claim 3 wherein the networked device is a controller device having a list of device types that the controller can control, further including:

determining the extent to which the controller can control the other device by determining the lowest level of device type that either is the device type of the other device or is a higher level device type from which the device type of the other device depends, in the list of device types that can be controlled by the controller;

and then controlling the other device with the functionality of the determined lowest level of device type by sending control signals selected from a list of control signals appertaining to the determined lowest level of device type.

5. A method according to claim 3 or 4 wherein the networked device is a controller device having a list of device types that the controller can control, further including:

receiving a controller query message from another device including an requested device type value to request whether the controller is able to control a device of the requested device type; and

responding with a controller response message including a device type value representing the lowest level of device type in the list of device types that either is the requested device type or is a higher level device type from which the requested device type depends.

6. A method of operation of a networked device, including:

receiving a simple device description query message from another device requesting a simple device description;

5 sending to the other device a simple device description message of fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type  
10 hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the  
15 controller device type.

7. A method according to claim 6 wherein the predetermined top level elements in the device type hierarchy further include a composite device type, and the networked device is of the composite device type having the  
20 functionality of an integer number of other devices, the method further comprising:

responding to a received simple device description query message by sending a simple device description message including the device type value representing the device as a composite device and further an integer sub-  
25 device number being the number of other devices.

8. A method according to claim 6 or 7 wherein the networked device is a bridge device for connection to first and second groups of devices, wherein the method further includes:

30 responding to a simple device description query message received from a device in the first group of devices by sending a simple device description message including a device type value representing the device as a composite

device and further an integer sub-device number being the number of other devices in the second group.

9. A method of operating a networked device, including:

5 receiving token-compressed messages;

recognising in the received token-compressed messages incoming simple device description query messages requiring a simple device description response from the networked device, without decompressing the incoming messages; and

10 sending a simple device description including a device type as a response to an incoming device query message requiring a simple device description response.

10. A networked device, including:

15 a transceiver for sending and receiving messages:

a message handler arranged to carry out the steps of:

establishing the address of at least one other device;

sending a simple device description query message another device requesting a simple device description;

20 receiving from the other device a simple device description message of fixed length including a device type value representing the type of the other device and a field indicating whether an extended device description is available;

and further arranged to optionally carry out the steps of:

25 testing the Simple device description message to determine whether an extended device description is available;

sending an extended device description query message to the other device requesting an extended device description from the other device; and

30 receiving from the other device an extended device description of variable length.

11. A networked device according to claim 10 wherein the simple device description message is in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

12. A networked device, including:  
a transceiver for sending and receiving messages;  
a message handler arranged to carry out the steps of:  
establishing the address of at least one other device;  
sending a simple device description query message to another devices requesting a simple device description;  
receiving from the other device a simple device description message of fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

13. A networked device, including:  
a transceiver for sending and receiving messages;  
a message handler arranged to carry out the steps of:

receiving a simple device description query message from another device requesting a simple device description; and

5 sending to the other device a simple device description message of fixed length, the simple device description message being in the form of a token-compressed message compressed from a human-readable message format, the message including a device type value representing the type of the other device; the device type value being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary  
10 device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

15 14. A networked device according to claim 13 wherein the networked device is a bridge device for connection to first and second groups of devices, the networked device further comprising a first transceiver for communicating with the first group of devices and a second transceiver for communicating with the second group of devices,

20 wherein the message handler is arranged to respond to a simple device description query message received from a device in the first group of devices by sending a simple device description message including a device type value representing the device as a composite device and further an integer sub-device number being the number of other devices in the second group.

25

15. A networked device according to claim 13 or 14 further comprising a memory storing a predetermined simple device description message precompressed from human readable format, wherein the message handler is arranged to read the predetermined simple device description  
30 message from the memory and send it through the transceiver in response to an incoming device query message.

16. A networked device, comprising  
a transceiver for sending and receiving token-compressed human  
readable messages; and

5 a message handler arranged to carry out the steps on incoming token-  
compressed human readable messages of: recognising received device query  
messages requiring a simple device description response from the networked  
device, without decompressing the incoming messages; and sending through  
the transceiver a simple device description including a device type as a  
response to an incoming device query message requiring a simple device  
10 description response.

17. A system, comprising

a plurality of networked devices each having a transceiver for sending  
and receiving network messages; wherein

15 each networked device has a predetermined device type selected from  
a device type hierarchy having predetermined top level elements including a  
controller device type and a basic device type, and at least one further level of  
subsidiary device types depending from the basic device type and inheriting  
properties of higher level device types on which the subsidiary device type  
20 depends, but not including any further level of subsidiary device types  
depending from the controller device type;

at least one of the networked devices has a controller device type; and

at least one of the networked devices has a device type of the basic  
device type or a device type depending from the basic device type.

25

18. A system, comprising

a plurality of networked devices each having a transceiver for sending  
and receiving network messages;

at least one networked device arranged to send a simple device query  
30 message to other devices and to receive and interpret simple device  
description messages subsequently received from the other devices;



at least one networked device arranged to send an extended device query message to other devices and to receive and interpret extended device description messages subsequently received from the other devices;

each of the networked devices being arranged to respond to an  
5 incoming simple device query message from another of the devices by sending a simple device description message of defined length including a device type value representing the type of the device; and

at least one of the networked devices is arranged to respond to an incoming extended device query message from another of the devices by  
10 sending an extended device description message.

19. A system according to claim 17 or 18, wherein the plurality of networked devices include at least one simple device without the capability to decompress messages and interpreting directly compressed messages and at  
15 least one complex device including a message decompression arrangement for decompressing the messages and a message interpreter for interpreting the decompressed messages.

20. A system according to claim 17, 18 or 19 wherein the  
20 predetermined top level elements further include a composite device type;

the system includes at least one networked device of the composite device type having the functionality of a predetermined number of other devices, the predetermined number being an integer greater than or equal to 2; and

25 each of the at least one networked device of the composite device type responds to an incoming device query message requiring a simple device description by sending a simple device description including the device type as a composite device and a sub-device number representing the predetermined number of other devices.

30

21. A system according to claim 18, 19, or 20, wherein the networked devices form a first network, the system further comprising a

second plurality of the networked devices arranged as a second network, wherein one of the networked devices is a bridge device in both the first and second networks, wherein the bridge device is arranged to respond to requests from the first network for a simple device description by responding  
5 with a simple device description including the device type as a composite device and a sub-device number representing the number of other devices in the second network.

22. A method of operating a network including controller devices and  
10 controlled devices, the method comprising:

establishing in a specific controller device a list of network addresses of devices in the network;

sending a query message requiring a simple device description response from the specific controller device to another of the devices;

15 sending from the other device to the specific controller device a simple device description message indicating the device type, wherein the device type is selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic  
20 device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type;

determining the extent to which the specific controller device can control the other device by determining the lowest level of device type that either is  
25 the device type of the other device or is a higher level device type from which the device type of the other device depends; and

controlling the other device by the specific controller device with the functionality of the determined lowest level of device type by sending control signals from the specific controller device to the other device selected from a  
30 list of control signals appertaining to the determined lowest level of device type.

23. A computer program for controlling a networked device, the computer program being arranged to cause the networked device to carry out the steps of a method according to any of claims 1 to 9.

5 24. A computer program for controlling a controller-type networked device, the networked device having a transport stack and an application, the computer program comprising:

code implementing a transport adaption layer for interfacing with the transport stack;

10 code implementing an application programming interface for interfacing with the application; and

code implementing a messaging layer including the capabilities of sending and receiving messages in a token-encoded human readable messaging format, the code being arranged to cause the networked device:

15 to recognise incoming device query messages requiring a simple device description response and to provide a simple device description response including a device type of controller device type;

to respond to an incoming controller query message querying whether the networked device can control a predetermined device type by responding  
20 with the lowest level of device type in the list of device types that can be controlled by the networked device that either is the predetermined device type or is a higher level device type from which the predetermined device type depends; and

to carry out the steps of:

25 sending a device query message to another device;

receiving a response from the other device indicating the device type of the other device, the device type being selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types  
30 depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including

any further level of subsidiary device types depending from the controller device type;

determining the extent to which the networked device can control the other device by determining the lowest level of device type that either is the device type of the other device or is a higher level device type from which the device type of the other device depends, in the list of device types that can be controlled by the networked device; and

controlling the other device with the functionality of the determined lowest level of device type by sending control signals selected from a list of control signals appertaining to the determined lowest level of device type.

25. A computer program for controlling a networked device, the networked device having a transport stack and an application, the computer program comprising:

code implementing a transport adaption layer for interfacing with the transport stack;

code implementing an application programming interface for interfacing with the application; and

code implementing a messaging layer including the capabilities of sending and receiving messages in a token-encoded human readable messaging format, the code being arranged to cause the networked device:

to recognise incoming device query messages requiring a simple device description response and to provide a simple device description response including a device type selected from a device type hierarchy having predetermined top level elements including a controller device type and a basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type; and

to respond to basic device instructions sent by a controller.

26. A computer program according to claim 23, 24 or 25 recorded on a data carrier.

27. A simple device description message signal, including in token-  
5 compressed XML the following data:

a predetermined number of bits storing a device type;

a field indicating if the sending device has an extended device description available; and

a defined number of additional fields identifying a defined number of  
10 additional status settings.

28. A simple device description message according to claim 27 wherein the device type is selected from a device type hierarchy having predetermined top level elements including a controller device type and a  
15 basic device type, and at least one further level of subsidiary device types depending from the basic device type and inheriting properties of higher level device types on which the subsidiary device type depends, but not including any further level of subsidiary device types depending from the controller device type.

20

29. A network establishment and management protocol for controlling electronic devices, the protocol being recorded on a record medium, the protocol comprising:

a compression algorithm defining the mechanism for compression of  
25 said messages

a definition of a generic message format, the messages being compressed XML compliant messages; and

a definition of message sequencing requirements.

30

30. A system in accordance with a network establishment and management protocol for combining electronic devices according to claim 27.

31. A method of operating a bridge device between first and second networks, there being a plurality of first network devices in the first network, a plurality of second network devices in the second network, one of the network devices being a bridge device in both the first and second networks, wherein  
5 the first network uses message signals including device descriptions of the network devices as being of one of a number of device types including a composite device type having a plurality of subdevices and wherein devices in the first network find further information regarding composite devices by sending further device queries relating to an individual subdevice and  
10 receiving from the composite device information relating to the individual subdevice; the method including:

receiving a device description query in the bridge device from the first network;

15 responding to the device description query with a device description message including the description of the bridge device as being of a composite device type and a value representing the number of other devices in the second network;

receiving at least one further device description query from a device in the first network relating to one of the other devices;

20 responding to the or each further device description query with a device description message including a description of the other device; and

forwarding in the first network further messages to or from devices in the second network from or to devices in the first network respectively as messages to or from the respective subdevice of the bridge device;

25 whereby network devices in the second network appear to network devices in the first network as sub-devices of the bridge device of composite device type.

32. A bridge device between first and second networks, there being  
30 a plurality of first network devices in the first network, a plurality of second network devices in the second network, one of the network devices being a bridge device in both the first and second networks, wherein the first network

uses message signals including device descriptions of the network devices as being of one of a number of device types including a composite device type having a plurality of subdevices and wherein devices in the first network find further information regarding composite devices by sending further device queries relating to an individual subdevice and receiving from the composite device information relating to the individual subdevice; the bridge device comprising:

a first transceiver for communicating with other devices in the first network;

a second transceiver for communicating with other devices in the second network;

and a message handler arranged:

to receive a device description query in the bridge device from the first network and to respond to the device description query with a device description message including the description of the bridge device as being of a composite device type and a value representing the number of other devices in the second network;

to receive at least one further device description query from the first network relating to one of the other devices; and to respond to the or each further device description query with a device description message including a description of the other device as a corresponding sub-device; and

to forward in the first network further messages to or from devices in the second network from or to devices in the first network respectively as messages to or from the respective subdevice of the bridge device;

whereby network devices in the second network appear to network devices in the first network as sub-devices of the bridge device of composite device type.

33. A computer program arranged to control a networked bridge device to carry out the method of claim 31.

34. A computer program according to claim 33 recorded on a data carrier.



## ABSTRACT

**A NETWORK ESTABLISHMENT AND MANAGEMENT PROTOCOL**

5

The invention relates to a protocol for communications between networked devices. The devices are logically arranged as a hierarchy of device types including a controller device type 52 from which no other device type depends and a basic device type 54 from which a number of other device types depend. The devices implement a simple device description message of fixed length and format which includes the device type, and some devices further implement an extended device description message including additional information.

15

[Figure 4]

1/6






Fig. 3





Fig. 5




Fig. 6

Fig. 7





Fig. 10




Fig. 8






Fig. 9






Fig. 13




Fig. 14




Fig. 15